



Corrosion Resistant ABC Multipurpose Dry Chemical Extinguisher

Introducing Badger's new line of corrosion resistant stored pressure fire extinguishers.

Designed specifically for applications where equipment is frequently exposed to harsh environments, these extinguishers feature a tough zinc chromate base coating covered with an epoxy powder paint to enhance corrosion resistance.

Badger CR extinguishers are perfect for heavy industry, petrochemical facilities, marine applications, food processing plants and other caustic chemical environments.

Badger dry chemical extinguishing agents contain the highest percentage of essential base ingredients found in the fire extinguisher industry.



BADGER^{CR}

Tough corrosion resistance

BADGER^{CR} - Corrosion Resistant Extinguisher



Cylinders feature a tough zinc chromate base coating

- 5, 10 and 20 pound models
- Zinc chromate base coated shell
- Laser welded cylinders
- Epoxy powder paint finish enhances corrosion resistance
- Stainless steel hose band and nozzle retainer
- UL Listed & U.S. Coast Guard Approved
- 12 year periodic hydrostatic test interval
- Plated brass valve and steel siphon tube
- Stainless steel handles and levers
- Badger Multipurpose Dry Chemical contains 90% M.A.P.
- Large loop stainless steel pull pin with tether

Technical Data: **BADGER**CR - Corrosion Resistant Dry Chemical Extinguisher Models

MODEL	B5M-CR			B10M-CR			B20M-CR		
PART NUMBER	24816			24821			24824		
CAPACITY (lb.)	5			10			20		
CAPACITY (kg)	2.3			4.5			9.1		
UL FIRE RATING	3A-40B:C			4A-80B:C			20A-120B:C		
AGENT TYPE	ABC			ABC			ABC		
CYLINDER MATERIAL	Zinc Chromated Steel			Zinc Chromated Steel			Zinc Chromated Steel		
VALVE MATERIAL	Plated Brass			Plated Brass			Plated Brass		
HANDLE/LEVER MATERIAL	Stainless Steel			Stainless Steel			Stainless Steel		
EXPELLANT	Nitrogen			Nitrogen			Nitrogen		
TEMPERATURE RANGE (F)	-40	to	120	-40	to	120	-40	to	120
TEMPERATURE RANGE (C)	-40.0	to	48.9	-40.0	to	48.9	-40.0	to	48.9
AGENT FLOW RATE (lb/sec)	0.39			0.51			0.75		
AGENT FLOW RATE (kg/sec)	0.2			0.2			0.3		
NOM. DISCHARGE TIME (sec)	14			22			28		
DISCHARGE RANGE (ft.)	12.0	to	18.0	16.0	to	20.0	16.0	to	20.0
DISCHARGE RANGE (m)	3.7	to	5.5	4.9	to	6.1	4.9	to	6.1
UNIT HEIGHT (in.)	15.25			18.94			21.13		
UNIT HEIGHT (cm)	38.7			48.1			53.7		
UNIT WIDTH (in.)	7.5			7.75			9.25		
UNIT WIDTH (cm)	19.1			19.7			23.5		
UNIT DEPTH (in)	4.25			5.25			7.25		
UNIT DEPTH (cm)	10.8			13.3			18.4		
SHIPPING WEIGHT (lb)	10.28			17.46			33		
SHIPPING WEIGHT (kg)	4.7			7.9			15.0		
USCG APPROVAL	Type A Size-II			Type A Size-II			Type A Size-II		
	Type B:C Size-I			Type B:C Size-II			Type B:C Size-III		
BRACKET	MB-5B			UB-10			UB-20		
	Optional			Optional			Optional		

Distributed by:



Badger Fire Protection
 4251 Seminole Trail • Charlottesville, VA 22911
 Tel 800 446 3857 or 434 973 4361
 Fax 800 248 7809 or 434 973 1589
www.badgerfire.com

 **A Kidde Company**

BFPN 0010